



Compressed Air Packages

AIRTOWER™ Series

From 3 to 7.5 hp



kaeser.com

Technical Specifications

Model	hp	Pressure Range	Capacity @ 125 psig (cfm)	Dimensions W x D x H (in.)	Weight (lbs.)	Noise Level (dB(A))	Power	
							Compressor ²	Dryer
AIRTOWER 3C ¹	3	80 - 160	- 160 12.0	24 ³ /8 x 38 ⁵ /8 x 58	628	69	208/230/460 V 3 phase 60 Hz	115 V 1 phase 60 Hz
AIRTOWER 4C ¹	4	80 - 217	15.9		628	70		
AIRTOWER 5C	5		21.2		639			
AIRTOWER 7.5C	7.5		28.3		661			

Standard pressures are 125, 160, and 217 psig, with minimum pressure band of 15 psi.

1 Available as special order

² AIRTOWER 5C and 7.5C also available 208-230 V/1 phase/60 Hz

Specifications subject to change without notice.

Life just got easier



Small footprint

- Vertical tank saves precious floor space
- Designed for corner placement

Easy installation

- Comes completely assembled
- Easily handled with fork truck or pallet jack
- Simple electrical connections for compressor and dryer
- Only one compressed air connection
- No need to fasten it to floor

Easy maintenance

- Routine fluid and filter changes
- Lightweight, one-piece cover gives easy access for service